

TECHNICAL DATA

SHARP 20 12/50 BATTERY CHARGER

STATED DATA ACCORDING TO MICROPOWER STANDARD

VARIABLE	
Part number	924132
Model	SHARP 20
Type	12/50
MAINS DATA (50/60HZ)	
Mains phase	1 Phase
Mains voltage supply	220-240
Max mains current (at min rated mains V) [A]	4,2
Recommended mains fuse [A]	16
Mains cable area [mm ²]	3x1,5
Mains cable length [m]	2,5
Mains connector	10A Schuko
BATTERY CONNECTION	
Battery cable [mm ²]	2x6
Battery cable connection (in charger)	Terminal
Battery cable length [m]	2,0
Battery connector (not included)	User defined
ELECTRIC DATA	
Standby power consumption [W]	<5
Power consumption [W]	909
Apparent power consumption [VA]	918
Power factor	0,99
Inrush current [A]	Negligible
Output ripple	<1
Efficiency (at rated power and no cables) [%]	85
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full capacity) [deg C]	-5 to +40
Ambient max temp (with reduced capacity) [deg C]	50
Cooling	Fan
Short circuit protection	Yes
Wrong polarity protection	Electronic
Cabinet type	P4

Certifications	CE
HMI	LED
HMI Language	-
Reporting	No
Charging curve set	10-04,06 & 20-09
I/O-cards	No
Accessories	See website

CHARGING TIMES

8 h [Ah]	383
10 h [Ah]	523
12 h [Ah]	665

CHARGER DIMENSIONS

Outer dimensions (HxWxD) [mm]	243x112x74
Charger weight excl. Cables [kg]	1,5
Charger weight incl. Cables [kg]	2,1

SHIPPING DIMENSIONS

Box size [HxWxD] [mm]	310x200x140
Shipping weight [kg]	2,6

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.